RX890 XXXX

TORQUE WRENCHES

Use:

-) Controlled screw tightening from 5 to 550 $\mbox{N}\cdot\mbox{m}$
- > For controlled bi-directional tightening
- > Repetition-accurate and precision-like
- > Torque triggering clearly to be heard and felt

Features:

- > Adjustable torque wrench with square drive and integrated ratchet-head function
- > Square drive with ratchet mechanism
- > Torque is set by turning the handle
- > The set value is fixed through the lock at the end of the handle
- ightarrow Easy-to-read scale with magnifying glass for N·m, plus 1/10 scale for precision setting
- > Actuation accuracy: +/- 3 % tolerance of the scale set torque

Scope of delivery:

- > Torque wrench with test certificate acc. to DIN EN ISO 6789
- > Operating instructions







R78900550	
K/8900550	7

Code	No.	Туре	"		N⋅m	1L. V·m	∢ mm ►	$\Delta_{kg}^{\dagger}\Delta$
3301214	R48900025	Plug-in square with knob, serrated	1/4	6.3	5-25	0.1	285	0.515
3301871	R58900050	Plug-in square with knob, serrated	3/8	10.0	10-50	2.5	335	0.540
3301216	R68900100	Plug-in square with knob, serrated	1/2	12.5	20-100	0.5	395	1.176
3301217	R68900200	Plug-in square with knob, serrated	1/2	12.5	40-200	1.0	485	1.350
3301218	R68900300	Plug-in square with knob, serrated	1/2	12.5	60-300	1.0	575	1.541
3301219	R78900400	Push-through square head with pin	3/4	20.0	80-400	1.0	685	2.390
3301220	R78900550	Push-through square head with pin	3/4	20.0	110-550	1.0	955	4.184

Accessories

RX899 XXXX

COUPLER

- > For use with tools with a square ratchet function
- > Coupler in acc. with DIN 3120
- > Chrome-vanadium steel



Code	No.	Туре	"		$\Delta_{kg}^{\dagger}\Delta$
3301221	R48990000	Plug-in square with knob, serrated	1/4	6.3	0.021
3301222	R58990000	Plug-in square with knob, serrated	3/8	10.0	0.022
3301223	R68990000	Plug-in square with knob, serrated	1/2	12.5	0.060
3301224	R78991000	Push-through square head with pin	3/4	20.0	0.133